305m RG6 Tri-shield Coaxial Cable Reel 06MM-E6T



E6T is an RG6 75 Ohm tri-shield coaxial cable for free-toair and pay-TV systems. It's approved for both domestic Foxtel satellite and Telstra cable networks. Tri-shield cables are slightly more flexible and easier to work with than quad-shield cable, making them very popular for everyday use. Available in 305m reels, E6Q is a 3GHz rated low loss coaxial cable with a copper-clad steel centre conductor for durability and three shielding layers to guarantee maximum signal protection and stability.

PAY TV APPROVED F30442



- » An RG6 metre marked cable with tri-shielding
- » Sold in a 305 metre reel
- » Suitable and approved for pay and digital TV
- » Foxtel (F30442) Telstra (739/28) and NBN approved

Technical Data 06MM-E6T

Construction				
Inner Conductor	Material	Copper Clad Steel Wire		
	Diameter	1.02±0.01		
	(mm)			
Insulation	Material	Physically Foamed PE		
	Diameter, mm	4.57±0.15		
Outer Conductor	1st shield	Bonded AI/PET/AI Tape		
		4.78 ±0.13		
	2nd shield	Al-Mg Alloy Wire Braid		
	3rd shield	Non-bonded AI/PET/AI Tape		
Jacket	Material	PVC		
	Diameter, mm	7.06±0.20		
Mechanical Properties				
Bending	Single	35		
Radius, mm	Typical	70		
Pulling Strength, N		200		
Adhesion Force, N		>22		
Electrical Properties				
Impedance, Ω		75±3		
DCR of Inner conductor,		102.0		
Ω/km		102.0		
DCR of outer conductor,		24.10		
Ω/km				
Capacitance, pF/m		54		
Propagation Velocity, %		82		
DC Breakdown Voltage,		5.0		
kV		0.0		
Insulation Resistance,		>1x10 ⁴		
M Ω ∙km				

	>95@5~1000MHz		
Screening Attenuation, dB	>85@1000~2000MHz		
	>75@2000~3000MHz		
Attenuation			
Frequency MHz	Max. attenuation		
	@20°C,dB/100m		
5MHz	1.90		
55MHz	5.25		
211MHz	10.00		
250MHz	10.82		
270MHz	11.04		
300MHz	11.64		
330MHz	12.26		
350MHz	12.63		
400MHz	13.61		
450MHz	14.43		
500MHz	15.29		
550MHz	16.08		
600MHz	16.73		
750MHz	18.54		
870MHz	20.04		
1000MHz	21.49		
1300MHz	24.49		
1450MHz	25.89		
1750MHz	28.67		
2150MHz	31.79		
2600MHz	35.30		
2832MHz	37.74		
3000MHz	38.84		
Return Loss, dB			
5-3000MHz	≥20		
Standards			
Operation	-40~+70°C		
UL 1581 UV Resistance	Compliant		
720h			
2011/65/EU	Compliant		