

H60 Field Strength Meter with Digital Processing 12MM-H60

The H60 is a professional-grade Teledes RF instrument for measuring DVB-T, DVB-C, DVBS/S2 and Analogue signals. The H60 features fibre optic input allowing the user to measure RF signals directly from an RFoG solution via the onboard optical receiver. With a wide range spectrum analyser to 3300 MHz and featuring real-time sweep, the H60 is the ultimate tool for professional installers. With the ability to power up devices directly from the instrument, you can tune and balance your network on the go.

Teledes

Features and Benefits

- » Full spectrum analysis with colour screen
- » Dolby digital compliant
- » Built in DC voltage insertion for powering amplifiers and LNB where satellite testing required
- » Multifunction signal analysis and compliant with DVB-T, DVB-S/S2, DVB-C, FM and Analog signals, Optical tests on 1310nm, 1490nm and 1550nm and 3.3GHz spectrum analyser
- » Full data log analysis
- » Conditional interface

12MM-H60 Specifications

Scan & Log w/ Automatic Channel Identification	Terrestrial/ CATV	Yes
	Satellite	Yes
Universal Auto Lock. DVB-T, DVB-C, DVB-S&S2		Yes
Q.A.L (QPSK Auto Lock)		Yes
Interfaces		HDMI, USB, SD card, Mini-DIN, CAM, FC/APC (F.O.)
USB SW Update		Yes
Latest Version HW & SW		Yes
Thumbwheel Navigation		Yes
Satellite Frequency Selection		IF, real RF, Channel and memory
Menu and Measurement Display		On-Screen-Display (OSD)
Teletext		Analog & Digital
One Screen Measurements		Yes
Pass/Fail Indicators		Yes
Real-time COMBO Mode		Yes
Dynamic Range	Terrestrial/ CATV	60dB
	Satellite	55dB
Fibre Optics Interface		Yes
HDMI Output		Yes
Spectrum Analyser		3.3GHz

