

2 Way 16dB High Isolation Tap for MATV, TDT and Satellite 17MM-DM32Q-16

Features and Benefits

- » Pay TV approved F31042
- » Return loss ≥ 10 dB
- » Tap loss 16dB
- » Frequency range 5-2400MHz
- » Power pass input to output
- » Compact housing for ease of installation



17MM-DM32Q-16 Specifications

	Frequency (MHz)	Typical Value (dB)
Insertion Loss (In-Out)	5-40	≤ 3.5
	40-692	≤ 3.5
	692-1000	≤ 3.5
	1000-1500	≤ 4.0
	1500-1860	≤ 4.5
Tap Loss (In-Tap)	1860-2400	≤ 5.0
	5-40	16.5 ± 2.0
	40-692	16.0 ± 2.0
	692-1000	16.0 ± 2.0
	1000-1500	16.0 ± 2.0
Reverse Isolation (Out-Tap)	1500-1860	16.5 ± 2.0
	1860-2400	16.5 ± 2.5
	5-40	≥ 25
	40-692	≥ 30
	692-1000	≥ 25
Mutual Isolation (Tap-Tap)	1000-1500	≥ 25
	1500-1860	≥ 25
	1860-2400	≥ 25
	5-40	≥ 25
	40-692	≥ 30
Return Loss (In/Out/Tap)	692-1000	≥ 30
	1000-1500	≥ 25
	1500-1860	≥ 25
	1860-2400	≥ 25
	5-40	≥ 10
	40-692	≥ 10
	692-1000	≥ 10
	1000-1500	≥ 10
	1500-1860	≥ 10
	1860-2400	≥ 10