TERRA 5 Wire Multiswitch 5 In 8 Out **Remote Powered** 21MM-MV508





Features and Benefits

- » Foxtel approved (F30822)
- » Suitable for large installations of satellite IF distribution systems
- » Length of the subscriber line up to 80 meters (must meet Pay TV provider specifications)
- » Four positions discrete gain regulator for each satellite IF line and separate 16 positions discrete gain regulator for terrestrial TV
- » Active terrestrial TV path powering from central power supply allows to receive terrestrial TV programs without switching on satellite TV receiver
- » Used with 5 Wire products only



Line Powered Specifications

Foxtel Approval Number		F30287		
Frequency Range	SAT IF	950-2400 MHz		
	Terr. TV	47-862 MHz		
SAT IF Gain	Outputs 1-4	5 ÷ 14dB		
(fixed slope pre- correction)	Outputs 5-8	4 ÷ 12dB		
Terr. TV Gain	Outputs 1-4	-1 ÷ 5dB		
(fixed slope pre- correction)	Outputs 5-8	-2 ÷ 3dB		
Gain Adjustment SAT IF		12dB by 4dB Step		
Gain Adjustment Terr. TV		15dB by 1dB Step		
Output Level for SAT IF (IMD3=35dB)*		105dBµV		

Output Level	Outputs 1-4	88dBµV	
for Terr. TV	Outputs F 0	06 dDV	
(IMD3=60dB)*	Outputs 5-8	86dBµV	
SAT Inputs Decoupling		≥30dB	
Outputs	SAT IF	≥30dB	
Decoupling	Terr. TV	≥35dB	
Rejection	Terr. TV/SAT	≥30dB	
	SAT/Terr. TV	≥40dB	
Consumption From Receiver		<65mA	
Consumption From Inputs H		110 V/ COme A	
Lines or External Power Supply		+18 V 60mA	
Control Signals		14/18V, 0/22kHz	
Dimensions		187 x 135 x 30mm	
Weight		0.6kg	

^{* 2} Equal Carriers

