

TERRA 5 Wire Splitter 2 Way 4 Satellite 1  
Terrestrial for TDT and Radial Multiswitches  
21MM-SD504TDT



Features and Benefits

- » The 21MM-SD504TDT is designed for splitting 5 input lines (4 satellite and 1 terrestrial TV) into 2 paths
- » Foxtel (F30921) approved
- » The splitter meets shielding requirements of class A according to standard EN50083-2
- » The splitter is intended for indoor use only
- » 21MM-SD504TDT consists of 5 highly isolated splitters for every input line. Splitter distribute signals into two equal parts, maintaining line matching properties and isolation between different paths.
- » Connectors on splitter can accept cables with central pin diameter up to 1.2mm



21MM-SD504TDT Specifications

Frequency range	SAT IF	950-2400 MHz
	Terr. TV	5-862 MHz
Through loss	SAT IF	4 dB
	Terr. TV	4 dB
Tap loss	SAT IF	4 dB
	Terr. TV	4 dB
SAT inputs decoupling	SAT IF	30 dB
	Terr. TV	30 dB
DC pass through	V line	0.5 A max.
	H line	1 A max.
	Terr. TV line	0.1 A max.
Return loss		> 10 dB
Operating temperature range		-20° ÷ +50°C
Dimensions/Weight (packed)		126x135x30mm/0.44kg