

9 Port Gigabit Managed Network Switch (8 Port PoE , 1 Uplink) 57MM-SW09P



The 57MM-SW09P is a PoE nine port gigabit managed network switch. The switch features nine ports with eight PoE+ ports, one gigabit uplink, 120W supporting 802.3af and 802.3at, providing up to 30W power supply to the connected device. In addition, the switch will negotiate with the connected devices to adjust the PoE power automatically, thereby saving energy.

3-Year Manufacturer's Warranty

Refer to website for full terms & conditions

Features and Benefits

- » Nine port managed network switch with eight PoE+ ports
- » The free cloud service supports smart networking features, allowing users to auto-provision, deploy and manage devices remotely.
- » Offers a 120W PoE budget and up to 30W per PoE port.
- » Supports port status display, port traffic statistics and PoE port output power status
- » Supports port duplex/negotiation rate configuration and flow control configuration
- » Supports PoE output on/off L2 features: Support port mirroring, loop protection and cable detection



9 Port Gigabit Managed Network Switch (8 Port PoE , 1 Uplink)

57MM-SW09P



Hardware specifications	
Ports	8x 10/100/1000 Mbps (PoE/PoE+) 1x 10/100/1000 Mbps
Maximum output power per PoE port	30W
Maximum PoE output power per switch	120W
Switching capacity	18Gbps
Packet forwarding rate	13.392Mpps
Surge protection	Common mode: 4KV
Electrostatic discharge	Air discharge: 6KV Contact discharge: 4KV
Power consumption	≤130W
Power supply	External power adapter
Dimensions (W x D x H)	202 x 108 x 28mm
MTBF	>200K
Operating environment	
Operating temperature	0°C to 40°C
Storage temperature	-40°C to 70°C
Operating humidity	10% to 90% RH
Storage humidity	5% to 90% RH
Software features	
MAC capacity	4K
Static MAC address	16
VLAN	Support 802.1Q VLAN
Port management	Support port status display, port traffic statistics, PoE port output power status, port duplex / negotiation rate configuration, flow control configuration, PoE output on/off
Security	Support broadcast storm suppression, port speed limit, port isolation
L2 features	Support port mirroring, loop protection, cable detection
Management	Support management and configuration through web management interface, Ruijie Cloud platform and mobile app