

Wideband optical splitters available in 19-inch rack mount and ABS box stand-alone series to build into wall and tray FOBOT's. Suitable for use in both data and MATV/ SMATV fibre networks. They are featuring an operating wavelength range of 1260-1650nm.

Features and Benefits

- » SC/APC angle-polished optical connectors as standard (other models available by special order)
- » Available from 2 way to 32 way in 19" rack or ABS box stand-alone form
- » All connectors on the front panel in 19" form for ease of access
- » Excellent polarization insensitivity
- » High-quality optical splitters for wideband performance with 1310nm, 1490nm and 1550nm systems
- » Return loss >55dB



Product Code	Output	Style
20MM-OSP2-19	2 Way	19" Rack Mounted
20MM-OSP4*2-19	4x2 Way	19" Rack Mounted
20MM-OSP8*2-19	8x2 Way	19" Rack Mounted
20MM-OSP4-19	4 Way	19" Rack Mounted
20MM-OSP2*4-19	2x4 Way	19" Rack Mounted
20MM-OSP4*4-19	4x4 Way	19" Rack Mounted
20MM-OSP6-19	6 Way	19" Rack Mounted
20MM-OSP8-19	8 Way	19" Rack Mounted
20MM-OSP16-19	16 Way	19" Rack Mounted
20MM-OSP32-19	32 Way	19" Rack Mounted
20MM-OSP2-SB	2 Way	Stand-alone ABS Box
20MM-OSP4-SB	4 Way	Stand-alone ABS Box
20MM-OSP6-SB	6 Way	Stand-alone ABS Box
20MM-OSP8-SB	8 Way	Stand-alone ABS Box
20MM-OSP16-SB	16 Way	Stand-alone ABS Box
20MM-OSP32-SB	32 Way	Stand-alone ABS Box