

10 Port Cloud Managed Router, 10 x Gigabit with up to 4 WAN RG-EG210G-E



The RG-EG210G-E is a 10 port Multi-WAN cloud-managed router with 8 x GbE Base-T ports. The router features one fixed WAN and six fixed LAN ports with three ports switchable. The RG-EG210G-E supports up to 200 concurrent client connections and supports WAN load balancing for increased input bandwidth (maximum 1 Gbps throughput) and redundancy. The RG-EG210G-E also supports Access point management for up to 150 APs.



3-Year Manufacturer's Warranty

Refer to website for full terms & conditions

Features and Benefits

- » 10 port WAN/LAN cloud-managed router with port load balancing for maximum throughput with built-in access point controller for up to 150 APs
- » Supports up to 200 concurrent clients with behaviour management and flow control policies
- » Free cloud management for monitoring and setup with simple operation and maintenance on the Ruijie Cloud App
- » Throughput - 1 Gbps with smart IP-based Automatic Bandwidth Assignment
- » Supports WAN load balancing and WAN port failover
- » VPN Server and Client support, IPsec, L2TP, PPTP, OpenVPN



10 Port Cloud Managed Router, 10 x Gigabit with up to 4 WAN RG-EG210G-E



Basic Specifications	
Fixed WAN Port	1 10/100/1000M Base-T ports
Fixed LAN Port(s)	9 10/100/1000M Base-T ports
LAN/WAN Switchable Port(s)	3 10/100/1000M Base-T ports
RAM	256 MB
Flash	16 MB
Recommended Clients	200
Recommended Bandwidth	1000 Mbps asymmetric bandwidth (flow control disabled) 1000 Mbps asymmetric bandwidth (flow control enabled)
Local Power Supply	Support 220V AC local power supply
Power Consumption	<15 W
Basic Network Features	
Network Access	PPPoE dial-up, DHCP client, Static IP, Automatic identification of access methods, Automatic avoidance of WAN port address conflicts, MAC cloning, Obtaining account passwords from existing routers
Routing	Static routing, Policy-based routing, Carrier address routing, Active/standby mode, Load, balancing based on source address, Flow-based load balancing, Port-based weighted load balancing of data streams
Hardware specifications	
Security	ACL, IP-MAC binding, MAC address filtering, dynamic ARP, static ARP binding, NAT, NAPT, port mapping
Other Protocols	DHCP Server, DHCP Client, DHCP Option43 / 138, DNS Client, DNS Server, DNS Proxy, NTP, DDNS
Gateway	
Application Recognition	Built-in self-developed application signature database to identify applications Automatic upgrade. Support free upgrades

Flow Control	Support custom flow control policies, IP-based automatic bandwidth assignment, Application-based automatic bandwidth assignment.
Traffic Audit	Real-time traffic audit, IP traffic visualization
Behavior Management	Time-based and IP policy-based access control, website filtering, App Control, User Management.
VPN	IPsec VPN (8 tunnels), L2TP(8 tunnels), PPTP(8 tunnels), Open VPN(16 tunnels)
Marketing Authentication	WiFiDog (SMS authentication and one-click authentication)
Local Authentication	Password authentication, QR code authentication, voucher authentication
Wireless Management	
Management Capacity	In AC mode,the maximum management capacity is 500 In gateway mode, the maximum management capacity is 150
AP Management	Support multi-SSID configuration, SSID hiding, channel setting, power setting, AP wired port setting, AP online upgrade, STA quantity setting, STA blacklist and whitelist
Roaming	Support local forwarding roaming, Layer 2 roaming, Layer 3 roaming between APs, viewing of STA roaming track
Switch management	
Management Capacity	Maximum manageable cloud managed switches: 128
Port Management	Loop protection, port mirroring, port isolation, port configuration, PoE configuration, port limit, storm control, static MAC, MAC search
Statue Display	Port statistics, monitoring information, cable detection, VLAN configuration, MAC list

10 Port Cloud Managed Router, 10 x Gigabit
with up to 4 WAN
RG-EG210G-E



Upgrade Management	Per-device upgrade, Batch upgrade
Value Added Features	
Featured Solutions	Single-cable IPTV solution port service VLAN and network segment isolation solution smart fault diagnosis solution intranet penetration solution auto-networking solution
Management	eWeb and Ruijie Cloud
Physical Specifications	
Dimensions	440 mm x 43.6 mm x 200 mm
Weight	2.35 kg
Temperature	Operating temperature: 0 ~ 40°C Storage temperature: -10°C ~ 70°C
Humidity	Operating humidity: 10% ~ 90% (non-condensing) Storage humidity: 5% ~ 95% (noncondensing)