28 Port Gigabit Layer 2 Smart Cloud-Managed PoE Network Switch (24x PoE+, 2x RJ45 GbE, 2x SFP), 250 W

RG-ES228GS-LP

The RG-ES228GS-LP is a 28-port Gigabit smart cloud-managed PoE switch designed for reliable business and CCTV networks. It features 26 Gigabit Ethernet ports, including 24 PoE/PoE+ ports with a 250 W power budget, plus two Gigabit SFP ports for fibre uplinks. Ruijie Cloud management enables remote monitoring and configuration, while camera recognition, PoE watchdog, automatic loop prevention and VLAN support simplify management and improve network reliability. Its fanless metal design supports quiet desktop or rack-mount installation.

3-Year Manufacturer's Warranty
For full terms & conditions, please see – Ruijie Warranty T&Cs.

Features and Benefits

- 24 Gigabit PoE/PoE+ ports with a 250 W power budget simplify connecting and powering IP cameras, access points, and other PoE devices.
- Two additional Gigabit Ethernet ports and two Gigabit SFP ports provide flexible high-speed copper and fibre uplink options.
- Lifetime-free Ruijie Cloud and Reyee App management enable convenient remote configuration, monitoring and maintenance.
- IP camera recognition and PoE watchdog simplify CCTV management and automatically restart unresponsive connected cameras.
- Automatic loop prevention helps avoid network disruptions and maintain reliable service continuity.
- Supports VLANs, port isolation, traffic control and storm control, improving network performance, organisation and security.

Specifications

Hardware Specifications

Power Supply and Consumption

PoE Out standard	PoE/PoE+ (IEEE 802.3af/at)
Number of PoE Out ports	24
Number of PoE/ PoE+ Out ports	24
PoE budget	250W
PoE power pins	1-2 (+), 3-6 (-)
Power input	220 V AC power supply: • Rated input voltage: 100 V AC to 240 V AC, 50 Hz to 60 Hz • Maximum input voltage: 90 V AC to 264 V AC, 47 Hz to 63 Hz • Rated input current: 6 A
Maximum power consumption	Less than 21W with no PoE load (110V) Less than 20W with no PoE load (220V) Less than 302W with PoE full load (110V) Less than 294W with PoE full load (220V)
Power supply	Fixed power supply

System Specifications

Flash memory	8 MB
Forwarding rate	41.664 Mpps
Switching capacity	56 Gbps(bit/s)

Environment and Reliability

Fan	1 x fixed fan
Cooling	Air cooling, front-to-rear airflow
Acoustic noise	< 40 dB: 25°C (77°F)
Mounting options	Desk/Rack
Hot swapping of cables	Hot swapping supported by the service port and power connector
MTBF	200,000 hours
Operating temperature	0°C to 40°C (32°F to 104°F)

28 Port Gigabit Layer 2 Smart Cloud-Managed PoE Network Switch (24x PoE+, 2x RJ45 GbE, 2x SFP), 250 W

RG-ES228GS-LP

Matchmaster
For the Best

Environment and Reliability (continued)

Storage temperature	–40°C to +70°C (–40°F to +158°F)
Operating humidity	10% RH to 90% RH (non-condensing)
Storage humidity	5% RH to 95% RH (non-condensing)
Altitude	–500 m to +5,000 m (–1,640.42 ft. to +16,404.20 ft.)
ESD protection	Air discharge: 8 kV Contact discharge: 6 kV
Surge protection	Service port: ±6 kV for common mode Power connector: ±6 kV for common mode and ±6 kV for differential mode

Dimensions and Weight

Casing	Metal
Product dimensions (W x D x H)	440 mm x 214.9 mm x 43.2 mm (17.32 in. x 8.46 in. x 1.70 in.)
Weight	2.80 kg (4.63 lbs) (without packaging materials) 3.85 kg (6.83 lbs) (with packaging materials)
Shipping weight	3.85kg (8.12 lbs)

Port Specifications

Total number of RJ45 ports	26
Total number of optical ports	2
Number of 1GE SFP ports	2
Number of 10/100/1000BASE-T ports	26
Reset button	1

Product Information

Warranty	3 years

Certification and Regulatory Compliance

EMC	EN 55032 EN 61000-3-2 EN 61000-3-3 EN 55035 EN 300 386
Safety compliance	EN 62638-1
Certification	CE, CB

Software Specifications

Authentication

RADIUS	No
802.1X authentication	No

Basic Configurations

PoE watchdog	Yes
Uninterruptible power supply upon warm start	No
Online upgrade	Yes

Gateway Features

802.1p priority-based traffic classification	No
DSCP priority-based traffic classification	No

Network Management and Monitoring

Fan speed adjustment	Automatic speed adjustment
Mirroring	Yes
HTTP login	Yes
HTTPS login	Yes
SON	Yes
Syslog	No
Camera detection	Yes
eWeb management	Yes
Ruijie Cloud management	Yes
Ruijie Reyee App management	Yes
SNMPv1, v2c, and v3	No

Security

Port isolation	Yes
Broadcast storm control	Yes
Multicast storm control	Yes
Unknown unicast storm control	Yes
DHCP snooping	Yes
Standard ACL	No

28 Port Gigabit Layer 2 Smart Cloud-Managed PoE Network Switch (24x PoE+, 2x RJ45 GbE, 2x SFP), 250 W

RG-ES228GS-LP

Matchmaster
For the Best

Security (continued)

Extended MAC ACL	No
Extended IP ACL	No
IPv6 ACL	No
ARP anti-spoofing	No
CPU Protection Policy	Yes

IP Service

ARP	No
IPv4 ping	No
IPv4 traceroute	No
ICMPv6	No
IPv6 ping	No
IPv6 traceroute	No
DNS client	Yes
DHCP client	Yes

Ethernet Switching

Maximum number of VLANs	16
Maximum number of MAC address entries	8000
Interface flow control	Yes
IEEE 802.1Q VLAN	Yes
VLAN configuration supported on LAN ports	Yes
LLDP	No
LLDP-MED	No
Static MAC address	Yes
Static aggregation	No
LACP	No
Inbound or outbound rate limiting based on interface traffic	Yes

Interface

Jumbo frame length (MTU)	10000 bytes
EEE	Yes
Cable test	Yes

IP Routing

IPv4 static route	No
IPv6 static route	No
OSPFv2	No
OSPFv3	No

Multicast

IGMPv1 snooping	No
IGMPv2 snooping	No
Basic IGMPv3 snooping	No
Full IGMPv3 snooping	No
IGMP filtering	No
IGMPv1, v2, and v3	No

System Performance Capacity

Recommended camera limit	200W H265: 80 400W H265: 40

Package Contents

Device

Device	1

Accessories

Rubber pad	4
Power cord retention clip	1
Screw	6 X M4 x 8 mm cross recessed countersunk head screws
Power cord	1 x 1.8 m (5.91 ft.)
Rack-mount bracket	2

Manual

User Manual	1
Warranty Card	1