

10 Port Gigabit Managed Network Switch (8 Port PoE, 2 x SFP) RG-NBS31-8G2S-P



The RG-NBS31-8G2S-P is a PoE 10 port gigabit managed network switch. The switch features ten ports with eight PoE+ ports and two SFPs, 125W supporting 802.3af and 802.3at, providing up to 30W power supply to the connected device. In addition, the switch will negotiate with the connected devices to adjust the PoE power automatically, thereby saving energy.

3-Year Manufacturer's Warranty

Refer to website for full terms & conditions



Features and Benefits

- » Ten port managed network switch with eight PoE+ ports
- » The free cloud service supports smart networking features, allowing users to auto-provision, deploy and manage devices remotely.
- » Offers a 125W PoE budget and up to 30W per PoE port.
- » Supports port status display, port traffic statistics and PoE port output power status
- » Supports port duplex/negotiation rate configuration and flow control configuration
- » Supports PoE output on/off L2 features: Support port mirroring, loop protection and cable detection



10 Port Gigabit Managed Network Switch (8 Port PoE, 2 x SFP)

RG-NBS31-8G2S-P



10/100/1000Base-T ports	8
SFP ports	2
SFP+ ports	No
PoE/PoE+ ports	8
Max. PoE budget	125W
Layer Type	Layer 2
Switching capacity	20 Gbps
Forwarding rate	14.88 Mpps
Packet Buffer	4.1 Mbit
MAC address table	8,000
Maximum VLAN Support	4094
Dimensions (W x D x H)	330 mmx 220 mm x 43.6 mm
Weight (With package)	2 kg
MTBF	> 200,000
Warranty	5 Years
Layer 2 Features	16
Jumbo Frame	9216
Flow Control	Yes
STP (IEEE 802.1d)	Yes
RSTP (IEEE 802.1w)	Yes
MSTP (IEEE 802.1s)	No
Port Fast	Yes
BPDU Guard	Yes
Errdisable Recovery	Yes
Max. Aggregation Group	8
Max. Member per Group	8
Unknown Unicast Storm Suppression	Yes
Multicast / Broadcast Storm Suppression	Yes
Many-to-One Mirroring	Yes
VLAN Range	1-4094
Port-based VLAN	Yes
MAC-based VLAN	Yes
IP-based VLAN	Yes
Voice VLAN	Yes
RLDP	Yes
LLDP / LLDP-MED	Yes
Cable Testing	Yes
IGMP Snooping v1/v2/v3	Yes
Software Features	
Ping	Yes
Traceroute	Yes
ACL Entries	1200
IP Standard ACL	Yes
MAC-based Extended ACL	Yes
IP-based Extended ACL	Yes
Port-based Rate Limit (Ingress/Egress)	Yes
SNMP v1/v2c/v3	Yes

10 Port Gigabit Managed Network Switch (8 Port PoE, 2 x SFP)

RG-NBS31-8G2S-P



802.1X	Yes
Web Management	Yes
Management IP	10.44.77.200
HTTP/HTTPS	Yes
Cloud Management	Yes
SON (Self-Organizing Network) with IP	Yes
Camera Recognition	Yes
Loop Prevention	Yes
Loop Notification	Yes
PoE Usage Alarm	Yes
Protection Port	Yes
IP Source Guard	Yes
Anti-ARP Spoofing	Yes
DHCP Snooping	Yes
DHCP Client	Yes
LACP (Q3,2023)	Yes
Physical Features	
Reset Button	Front
Cable Hot-swappable	Yes
Power Supply Slot	Single, fixed power supply
Power Supplies	100 - 240V AC, 2A
Power Consumption	≤ 145W
EEE	Yes
Fan	No
Airflow	No
Fan Adaptive Speed Adjustment	No
Acoustic Noise	Noiseless
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating Humidity	10% to 90% RH
Storage Humidity	5% to 95% RH
Port Surge	6 kV
Operating Altitude (meters)	-500 to 5000
Certificate	CE, RoHS